



Courflex®



APPLICATION STANDARDS: EN 61386-1/2004, EN 61386-23/2004

GENERAL DESCRIPTION:

- Made of polyvinyl chloride – (P-PVC), reinforced with a spiral made of polyvinyl chloride – (U-PVC).
- Self extinguishing; flame retardant.
- UV protection.
- In floor, wall mounted installations – Equipment manufacturing.
- Air Conditioning drainage.

Courflex®



CODE	TYPE	DIMENSIONS		COLOR	U.M.	LENGTH	PACKAGING
		EXT Ø mm	INT Ø mm				
16-21060-010	10	13,3	10	GRAY	M	30	30
16-21012-012	12	16	12	GRAY	M	30	30
16-21013-014	14	16,3	13,9	GRAY	M	30	30
16-21014-016	16	20	16,2	GRAY	M	30	30
16-21015-018	18	21,2	18,1	GRAY	M	30	30
16-21016-020	20	22,5	20,2	GRAY	M	30	30
16-21017-022	22	25,3	22	GRAY	M	30	30
16-21018-025	25	28,1	25,2	GRAY	M	30	30
16-21019-030	30	36	30	GRAY	M	30	30
16-21070-032	32	37	32	GRAY	M	30	30
16-21021-038	38	44,5	38,2	GRAY	M	30	30
16-21071-040	40	47	40	GRAY	M	30	30
16-21022-050	50	55,5	50	GRAY	M	30	30
16-21023-062	62	69	62,3	GRAY	M	30	30



GENERAL DESCRIPTION

- Flexible spiral
- Made of polyvinyl chloride – (P-PVC), reinforced with a spiral made of polyvinyl chloride – (U-PVC).
- Suitable for light mechanical loads
- Self extinguishing; flame retardant.

APPLICATIONS

- Residential and industrial installations.
- Infloor, wall mounted installations – Equipment manufacturing.
- Air Conditioning drainage.
- Connection with gland - Racor Courflex®.
- Fits with: Gland - Racor Courflex®, Watertight Boxes, Watertight External Elements IP 54.

PROPERTIES

Resistance to compression - (compression force) at 22 ±2 °C	> 320 N / 5cm	2
Resistance to Impact - (Weight mass / Fall Height) at -15 °C	m:1kg / h:100mm	3
Minimum temperature limit	-20° C	4
Maximum temperature limit	+60° C	1
Dielectric strength	2 kv / 15 min	
Insulation resistance	> 100 MΩ	


CLASSIFICATION

2
3
4
1



APPLICATION STANDARDS: EN 61386-1/2004, EN 61386-23/2004

AVAILABLE COLORS: WHITE, BLUE, BLACK



Joint Courflex®



CODE	TYPE	DIMENSIONS		COLOR	U.M.	PACKAGING	PACKAGING
		EXT Ø mm	INT Ø mm			(Bag)	(Box)
33-20008-012	12	D23	12	GRAY	PCS	10	1200
33-20009-016	16	D23	16	GRAY	PCS	10	800
33-20010-020	20	D29	20	GRAY	PCS	10	600
33-20011-020	25	D37	25	GRAY	PCS	10	300
33-20012-032	32	D37	32	GRAY	PCS	10	200

GENERAL DESCRIPTION

- Connection of watertight boxes with flexible Conduits Courflex®.
- Water tightness lever: IP 65.
- With fixing nut - Metric thread.

